Amendments to the claims are as follows:

1. (Original) An electronic circuit unit, comprising:

a circuit board having an upper face on which electronic components are mounted to form a desired electric circuit and a lower face having a plurality of first land portions connected to the electric circuit; and a connector member disposed at a lower portion of the circuit board;

wherein the connector member has an insulating resin portion, a metallic shield plate embedded in the insulating resin portion, and connector terminals which are provided with first terminals protruding from an upper face of the insulating resin portion and second terminals protruding from a lower face of the insulating resin portion; and

wherein the connector terminals are configured such that the first terminals over the upper face are electrically connected to the first land portions and the second terminals over the lower face are electrically connectable to second land portions of a mother substrate.

- 2. (Original) The electronic circuit unit according to Claim 1,
 wherein the shield plate has a plurality of cutout portions, and
 the connector terminals are arranged to pass through the cutout portions
 vertically without contacting the shield plate.
- 3. (Original) The electronic circuit unit according to Claim 1,
 wherein the connector member has earth terminals which are
 electrically connected to the shield plate, and the earth terminals are
 electrically connectable to the second land portions of the mother substrate.
- 4. (Original) The electronic circuit unit according to Claim 1, wherein the connector terminals are made of metallic plates, and are formed by the second terminals deformably extending from an outer surface of the insulating resin portion.

- (Original) The electronic circuit unit according to Claim 1, wherein the first land portions and the first terminals are soldered.
- 6. (Currently Amended) The electronic circuit unit according to Claim 1,

wherein the circuit board includes connecting pieces soldered to the first land portions; the connecting pieces are made of metallic thin plates; the connecting pieces have first connections soldered to the first land portions, second connections soldered to the first terminals, and legs linking the first and second connections; and the first land portions and the first terminals are soldered by the legs while they are separated.